



HS-58H Series thermal Receipt Printer Datasheet

Function

- Product Name: Receipt Printer
- Model: HS-58H
- Fashionable design, Splendid quality
- High-speed printing, High performance
- Support Logo download and print
- Support GB 18030
- International language
- Support the ESC/POS Command
- Support USB, Serial, Bluetooth interface
- Printer with CE, FCC, ROHS Certification
- Support windows, Linux, Android, IOS



Interface

Model	Interface	Remark
HS-58HU	USB	
HS-58HS	Serial	
HS-58HUI	USB+Bluetooth	IOS+Android+Windows

Package

One set size : 193*138*125mm
 24set/carton
 one set weith: 0.85kg
 carton size: 50*40*39cm
 Carton weight: 22

Application



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post

HSPOS TECHNOLOGY LIMITED

5 floor, A1 building, Nanshui industrial park, Sanjiao
Town, Zhongshan City, Guangdong Province, China

Tel +86 0760-85402097 Fax +86 0760-85402097

Website: www.hsprinter.com

Email: mikepeng@hsprinter.com



Parameters

Printing	
Printing method	Direct thermal
Print width	48mm
Column capacity	384 dots/line, 8dots/mm
Printing speed	90mm/s
Interface	USB,USB+Bluetooth
Printing paper	57.5±0.5mm×φ60mm
Line spacing	3.75mm (Adjustable by commands)
Column number	58mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese,traditional Chinese - 16 columns
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)
Barcode Character	
Extension character sheet	PC347/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/P C737/WPC/1257/ThaiVietnam/PC864/PC1001(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
Power	
Power adaptor	Input: AC 110V/220V, 50~60Hz
Power source	Output: DC 12V/2A
Cash drawer output	DC 12V/1A
Physical characteristics	
Weight	590g
Dimensions	185×130×112mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0~45℃) humidity(10~80%)
Storage environment	Temperature(-10~50℃) humidity(10~90%)
Reliability	
Printer head life	50KM