

HSPOS TECHNOLOGY LIMITED

5 floor, A1 building, Nanshui industrial park, Sanjiao Town, Zhongshan City, Guangdong Province, China

Tel+86 0760-85546950 Fax+86 0760-85546950

Website: www.hsprinter.com

Email: info@hsprinter.com



HS-KL80 Series Thermal Receipt Printer with cutter

Function

- Item Name: Thermal Receipt Printer
- Suitable for all types of commercial retail POS systems
- Light in weight and smart in shape
- High-quality printing and low cost
- Low noise and high-speed printing
- Support cash drawer driver
- Support auto cutter paper
- Easy for paper installation, Easy maintenance and excellent structure
- Low power consumption and low operating costs (No Ribbons or Ink cartridges)
- Fashionable design, Splendid quality
- High-speed printing, High performance
- Support Logo download and print
- International language
- support USB, serial, parallel, LAN, Bluetooth interface(optional)
- Support Windows (Win10/ WIN7/WIN8/Vista/XP/2000) Ubuntu 12.04 32/64, Ubuntu 14.04 32/64



Application



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post



Parameters

Printing method	Direct thermal
Print width	72mm
Column capacity	384 dots/line
Printing speed	100mm/s
Interface	USB/ USB+LAN/USB+Bluetooth/USB+Serial+LAN
Printing paper	80 ± 0.5mm × φ 80mm
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese, traditional Chinese - 16 columns
Character size	ANK, Font A: 1.5 × 3.0mm (12 × 24 dots) Font B: 1.1 × 2.1mm (9 × 17 dots) Chinese, traditional Chinese: 3.0 × 3.0mm (24 × 24 dots)
Barcode Character	
Extension character sheet	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251) etc.... 26 languages
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128
Buffer	
Input buffer	receive buffer area 1M bytes
NV Flash	NV bitmap 64K bytes
Power	
Power adaptor	Input: AC 110V/220V, 50~60Hz
Power source	Output: DC 12V/2.6A
Cash drawer output	DC 12V/2.5A
Physical characteristics	
Weight	0.88KG
Dimensions	180 × 135 × 135mm (D × W × H)
Environmental Requirements	
Work environment	Temperature (0~45) humidity(10~80%)
Storage environment	Temperature(-10~60℃) humidity(10~80%)
Reliability	
Printer head life	100KM
Auto cutter	Yes (Optional)