



HS-585 Series Portable Thermal Printer

Function

- ◆ Mini size, Light weight, Durable performance
- ◆ 2000mAH, 7.4V rechargeable li-ion battery, quick charge
- ◆ Continuously work for 6 -8hours one time Recharge
- ◆ Support various languages, easy to use
- ◆ Standard interface: USB(Virtual Serial), Bluetooth, (Apple and Android)
- ◆ Support Dots Printing With different densities
- ◆ Support raster Bitmap Print
- ◆ Support 2D and 1D QR CODE Printing
- ◆ Support OEM/ODM.
- ◆ Support Windows (Win10/ WIN7/WIN8/Vista/XP/2000)
Ubuntu 12.04 32/64, Ubuntu 14.04 32/64 drivers.
- ◆ Wonderful SDK templates For Linux(C++), Windows, Android, IOS



Application



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post

HSPOS TECHNOLOGY LIMITED
 5 floor, A1 building, Nanshui industrial
 park, Sanjiao Town, Zhongshan City, Guangdong Province, China
Tel +86 0760-85402097 **Fax** +86 0760-85402097
 Website: www.hsprinter.com
 Email: info@hsprinter.com



Parameters

Print	Printing Method	Thermal Line
	Printing Speed	50-80mm/s
	Resolution	8 dots/mm, 384 dots/line
	Effective Printing Width	48mm
Communication	Wired	Standard: Mini-USB Port, Optional : Serial Port(PS/2)
	Wireless	Bluetooth
Character	Character Set	ASCII 9*17, 12*24, GB2312-80(Chinese)
	Print Font	ANK: (8x16, 9x17, 9x24, 12x24) , GBK: 16x16, 24x24
	Language(Code Page)	Support Simplified & Traditional Chinese, English and other 45 kinds of International Character Sets
Paper Spec	Paper Type	Thermal paper
	Paper Width	57.5± 0.5mm
	Paper Roll Diameter	Max: 40mm
Softwares	Drivers	Windows(win10/ win8/win7/vista/xp/2000); Ubuntu 12.04 32/64 Ubuntu 12.04 32/64 Ubuntu 14.04 32/64
	App	Printer setting tools
Barcode	1D	UPC-A, UPC-E, EAN-8, EAN13, CODE39, ITF, CODEBAR, CODE128 Etc..
	2D	QR Code
Indicators LED		Power(red), Battery Charging(Green), Bluetooth and out of paper(Blue)
Paper tore		Manual
Detection Sensor		Out of Paper
Battery		Rechargeable Li-ion Battery, 7.4V, 2000mAh
Charger Power Supply (Adapter)		Input: 100-240VAC/0.5A, 50/60Hz; Out Put: 12Vdc/1A
Print Head Life		50km
Environment	Operating Temp	5°C ~ 50°C
	Operating Humidity	10% ~ 80%
	Storage Temp	-20°C ~ 60°C
	Storage Humidity	10% ~ 90%

HSPOS TECHNOLOGY LIMITED
5 floor, A1 building, Nanshui industrial
park, Sanjiao Town, Zhongshan City, Guangdong Province, China
Tel +86 0760-85402097 **Fax** +86 0760-85402097
Website: www.hsprinter.com
Email: info@hsprinter.com



Standard Accessory

- 1* User Manual,
- 1* Power Adapter
- 1* USB Data Cable
- 1* Test Paper Rolls
- 1* battery