

HSPOS TECHNOLOGY LIMITED
5 floor, A1 building, Nanshui industrial park, Sanjiao
Town, Zhongshan City, Guangdong Province, China
Tel +86 0760-85546950 **Fax** +86 0760-85546950
Website: www.hsprinter.com
Email: mikepeng@hsprinter.com



HS-QR702 Series thermal Receipt Printer Datasheet

Function

Feature:

1. Fashionable, delicate and elegant
2. Low noise direct thermal printing method
3. Various image/curves/characters printing function
4. Paper out detection, automatic memory printing function
5. Serial(RS232, TTL)/Parallel interface
6. High speed and low power consumption optional
7. Support low-voltage system
8. Installation dimension: 77x53x43mm
9. Outline dimension: 82x58x45mm



Application



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post



Parameters

Print	Printing Method	Thermal Line
	Printing Speed	50-80mm/s
	Resolution	8 dots/mm, 384 dots/line
	Effective Printing Width	48mm
Character	Character Set	ASCII, GB2312-80(Chinese)
	Print Font	ANK: (8x16, 9x17, 9x24, 12x24), GBK: 16x16, 24x24
Paper Spec	Paper Type	Thermal paper
	Paper Width	57.5± 0.5mm
	Paper Roll Diameter	Max: 50mm
Reliability	MCBF	5 million lines
Interface		Serial(RS-232, TTL),
Insert Depth		34.65mm
Power Supply (Adapter)		DC5V-9V/12V
Physical	Outline Dimension (WxDxH)	82x58x45mm
	Installation Port Size	77x53x43mm
	Color	Beige/Black(can be customized)
Environment	Operating Temp	5°C ~ 50°C
	Operating Humidity	10% ~ 80%
	Storage Temp	-20°C ~ 60°C
	Storage Humidity	10% ~ 90%