

HSPOS TECHNOLOGY LIMITED
5 floor, A1 building, Nanshui industrial
park, Sanjiao Town, Zhongshan City, Guangdong Province, China
Tel+86 0760-85546950 **Fax**+86 0760-85546950
Website: www.hsprinter.com
Email: mikepeng@hsprinter.com



HS-591AI 58mm Portable Thermal Printer

Function

1. Mini size, Light weight, Durable performance
2. 1500mAh, 7.4V rechargeable li-ion battery, quick charge
3. Continuously work for 6 hours or 200km
4. 80mm/s high printing speed
5. Support various languages, easy to use
6. Standard interface: USB, Bluetooth (Apple and Android)
7. Support Dots Printing With different densities
8. Support raster Bitmap Print
9. Support 2D and 1D QR CODE Printing



Application



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post



Parameters

Print	Printing Method	Thermal Line
	Printing Speed	50-80mm/s
	Resolution	8 dots/mm, 384 dots/line
	Effective Printing Width	48mm
Communication	Wired	Standard: Mini-USB Port, Optional : Serial Port(PS/2)
	Wireless	Bluetooth
Character	Character Set	ASCII9*17, 12*24, GB2312-80(Chinese)
	Print Font	ANK: (8x16, 9x17, 9x24, 12x24), GBK: 16x16, 24x24
	Language(Code Page)	Support Simplified & Traditional Chinese, English and other 45 kinds of International Character Sets
Paper Spec	Paper Type	Thermal paper
	Paper Width	57.5± 0.5mm
	Paper Roll Diameter	Max: 40mm
Softwares	Drivers	Windows(win10/ win8/win7/vista/xp/2000); Ubuntu 12.04 32/64 Ubuntu 12.04 32/64 Ubuntu 14.04 32/64
	App	Printer setting tools
Barcode	1D	UPC-A, UPC-E, EAN-8, EAN13, CODE39, ITF, CODEBAR, CODE128 Etc..
	2D	QR Code
Indicators LED		Power(red), Battery Charging(Green), Bluetooth and out of paper(Blue)
Paper tore		Manual
Detection Sensor		Out of Paper
Battery		Rechargeable Li-ion Battery, 7.4V, 1500mAh
Charger Power Supply (Adapter)		Input: 100-240VAC/0.5A, 50/60Hz; Out Put: 12Vdc/1A
Environment	Operating Temp	5°C ~ 50°C
	Operating Humidity	10% ~ 80%
	Storage Temp	-20°C ~ 60°C
	Storage Humidity	10% ~ 90%